



coatings

TECHNICAL DATA SHEET

Distributed by:

Dy-Mark (Aust) Pty Ltd

PO Box 1556 • Toowong QLD 4066

Phone: 1300 396 275 Fax: 1300 360 440 www.dymark.com.au



Smart Spray Survey Marker

Smart Spray Survey Marker is a fast drying paint designed for all marking applications. Designed for inverted use, Survey Marker is ideal for the surveying, construction and civil works industries.

DIRECTIONS FOR USE

Preparation

Shake can for 20 seconds after the mixing ball begins to rattle.

Application

Aerosol can must be used in the inverted position. Hold can approximately 10 – 15cm from surface.

TECHNICAL DATA

Size:	350g Aerosol
Finish:	Matt
Colour:	Red, Blue, Yellow, White, Fluoro Red, Fluoro Green, Fluoro Orange, Fluoro Pink
Consistency:	Liquid
Coverage:	Will produce approximately 200 'X' marks, 80 - 100m in a 50mm continuous line, or cover 4 - 6 sqm.
Suitable Surfaces:	Concrete, grass, bitumen, steel, timber
Drying Time:	5 minutes at 25°C
Ideal Application Temperature:	Between 10°C and 40°C

STORAGE

Store below 50°C. Do not store in direct sunlight or in vehicles under hot conditions.

DISPOSAL

Aerosol should be completely emptied prior to disposal. Contents of can are under pressure. Do not puncture or incinerate even when empty. When empty, dispose of this container through an approved recycling scheme or seek advice from your local council regarding accepted disposal methods.

SAFETY INFORMATION

HIGHLY FLAMMABLE

Keep away from flame, heat and sources of ignition. Do not smoke and ensure adequate ventilation during use. Harmful by inhalation, in contact with skin and if swallowed. Intentional misuse by deliberately inhaling contents can be harmful or fatal.

FIRST AID

KEEP OUT OF REACH OF CHILDREN

If swallowed: Do not induce vomiting

Eye contact: In case of contact with eyes, rinse immediately with plenty of water. Seek medical advice from your doctor or Poisons Information Centre.

The data provided within this Technical Data Sheet is intended as a guide only. The performance of the product will vary depending on differing operating conditions and application methods. For additional information, please see the Material Safety Data Sheet.