

TECHNICAL DATA SHEET



Dy-Mark (Aust) Pty Ltd
PO Box 1556 Toowong 4066
Phone: 1300 396 275 Fax: 1300 360 440
www.dymark.com.au

Spray & Mark



Dy-Mark Spray & Mark is a premium marking out paint designed for a range of applications including; construction, landscaping, civil works and surveying.

Spray & Mark is suitable for use with the Long Arm Handle and 2 Wheel Spot Marking Handle, also available from Dy-Mark.

DIRECTIONS FOR USE

Suitable Surfaces

Concrete, bitumen, steel and timber.

Ideal Application Temperature

Between -10°C and 40°C. Avoid use in windy conditions.

Before use

Refer to Technical Data Sheet and Safety Data Sheet before use.

Application

Before spraying, **Shake can** for at least 45 seconds **AFTER** the mixing ball begins to rattle. Shake can occasionally during use. Hold can in the **INVERTED** position (**upside down**), approximately 10-15cm from the surface. Spray width can be adjusted by moving closer or further from the surface to be sprayed.

Drying Time

Touch dry in 5 minutes (25°C).

Drying will be slower in cold and humid conditions, in the absence of ventilation or where heavy film build is applied.

After Spraying

Prevent blocking by holding the can **UPRIGHT** and spraying until only clear gas escapes. Also **wipe spray tip** of nozzle clean. **Clean up** wet paint with **Dy-Mark Acetone or General Purpose Thinner**.

TECHNICAL DATA SHEET



Dy-Mark (Aust) Pty Ltd
PO Box 1556 Toowong 4066
Phone: 1300 396 275 Fax: 1300 360 440
www.dymark.com.au

TECHNICAL DATA

Size:	350g Aerosol
Finish:	Matt
Colour:	9 Standard and 7 Fluoro colours
Consistency:	Liquid
Coverage:	Will produce 200 'X' marks, 80-100m in a 50mm continuous line, or cover 4-6 m ² .
Clean Up:	Dy-Mark Acetone or General Purpose Thinner

STORAGE

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C. (Do not store in or in vehicles under hot conditions). Store in a well ventilated place.

DISPOSAL

Pressurised container: Do not pierce or burn, even after use. Aerosol should be completely emptied prior to disposal. Dispose of contents/container according to regional regulations.

FIRST AID/SAFETY INFORMATION

Please refer to Safety Data Sheet before use. Safety data sheets are available for download from our website www.dymark.com.au or from following QR code:



Call a POISON CENTRE: Australia 13 11 26, New Zealand 0800 764 766 or doctor/physician if you feel unwell.

Intentional misuse by deliberately inhaling contents can be harmful or fatal.

Keep out of reach of children.

TECHNICAL DATA SHEET



Dy-Mark (Aust) Pty Ltd
PO Box 1556 Toowong 4066
Phone: 1300 396 275 Fax: 1300 360 440
www.dymark.com.au

DISCLAIMER

The information provided within this Technical Data Sheet is intended as a guide only. The Slip resistance and performance of this product depends on many factors outside the control of Dy-Mark; including surface preparation, surface-specific conditions, surface types, correct application and environmental conditions.

Dy-Mark recommends customers undertake their own risk assessment prior to use to determine the suitability of the product for the particular use intended. Some factors to consider:

- Slip resistance required
- Surface type
- Volume of traffic
- Potential exposure to any surface contaminants eg. Water, solvents or chemicals

It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information regarding the products slip resistance, please contact the Dy-Mark Sales and Customer Support Centre on 1300 396 275.